



## Outdoor Long-Range Wi-Fi 6 Access Point

### GWN7660LR

The GWN7660LR is an outdoor 802.11ax Wi-Fi 6 access point designed to provide next-generation long-range network coverage for medium-to-large indoor and outdoor environments. It offers IP-66 weatherproof certified casing, heat resistant technology, dual-band 2x2:2 MU-MIMO technology and a sophisticated antenna design for extended coverage range of up to 250 meters. It uses a controller-less distributed network management architecture in which the controller is embedded within the product's web user interface for easy administration of locally deployed Wi-Fi APs. The GWN Series is supported by GWN.Cloud and GWN Manager, Grandstream's cloud and on-premise Wi-Fi management platform that streamlines monitoring and maintenance, and makes managing your network or several networks across multiple locations easier than ever before. The GWN7660LR is the ideal Wi-Fi AP for voice-over-Wi-Fi deployment and offers a seamless connection with Grandstream's Wi-Fi capable voice and video IP phones. With support for advanced QoS, low-latency real-time applications, mesh networks, captive portals and dual Gigabit networks ports with PoE/PoE+; the GWN7660LR is an ideal outdoor Wi-Fi access point for enterprises, multiple floor offices, warehouses, parks, hospitals, schools and more.



**Gigabit**

1.77Gbps aggregate wireless throughput and 2x Gigabit Ethernet ports



**2x2  
MIMO**

Dual-band 2x2:2 MU- MIMO with DL/UL OFDMA technology



**PoE**

Self power adaptation upon auto detection of PoE or PoE+



Support 256+ concurrent Wi-Fi client devices



**250  
meters**

Up to 250-meter coverage range



**QoS**

Advanced QoS to ensure real-time performance of low-latency applications



Anti-hacking secure boot and critical data/control lockdown



Flexibility of 2 detachable/changeable antennas for different application scenarios



Embedded controller manages up to 50 local GWN APs; GWN.Cloud offers unlimited AP management, & GWN Manager offers on-premise software AP management

<b>Wi-Fi Standards</b>	IEEE 802.11 a/b/g/n/ac/ax
<b>Antennas</b>	2 dual band external antennas 2.4GHz, gain 3.5dBi 5 GHz, gain 3.5dBi
<b>Wi-Fi Data Rates</b>	<b>5G:</b> IEEE 802.11ax: 7.3 Mbps to 1201 Mbps IEEE 802.11ac: 6.5 Mbps to 867 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11a: 6, 9, 12, 18, 24, 36, 48, 54 Mbps <b>2.4G:</b> IEEE 802.11ax: 7.3 Mbps to 573.5 Mbps IEEE 802.11n: 6.5Mbps to 300Mbps IEEE 802.11b: 1, 2, 5.5, 11 Mbps IEEE 802.11g: 6, 9, 12, 18, 24, 36, 48, 54 Mbps  <i>*Actual throughput may vary depending on many factors including environmental conditions, distance between devices, radio interference in the operating environment and mix of devices in the network</i>
<b>Frequency Bands</b>	2.4GHz radio: 2412 - 2484 MHz 5GHz radio: 5180 - 5825 MHz <i>*Not all frequency bands can be used in all regions.</i>
<b>Channel Bandwidth</b>	2.4G: 20 and 40 MHz 5G: 20, 40 and 80 MHz
<b>System Security</b>	WEP, WPA/WPA2-PSK, WPA/WPA2 Enterprise (TKIP/AES); WPA3, anti-hacking secure boot and critical data/control lockdown via digital signatures, unique security certificate and random default password per device
<b>MU-MIMO</b>	2x2:2 2.4GHz, 2x2:2 5GHz
<b>Coverage Range</b>	Up to 250 meters <i>*Coverage range can vary based on environment</i>
<b>Maximum TX Power</b>	5G: 26dBm 2.4G: 30dBm <i>*Maximum power varies by country, frequency band, and MCS rate</i>
<b>Receiver Sensitivity</b>	<b>2.4G</b> 802.11b: -99dBm@1Mbps, -90dBm@11Mbps; 802.11g: -93dBm @6Mbps, -77dBm@54Mbps; 802.11n 20MHz: -74dBm @MCS7; 802.11n 40MHz:-72dBm @MCS7; 802.11ax 20MHz: -64dBm @ MCS11; 802.11ax 40MHz: -62dBm @MCS11 <b>5G</b> 802.11a: -95dBm @6Mbps, -77dBm @54Mbps; 802.11ac 20MHz: -71dBm@MCS8; 802.11ac: HT40:- 67dBm @MCS9; 802.11ac 80MHz: -64dBm @MCS9; 802.11ax 20MHz: -63dBm @ MCS11; 802.11ax 40MHz: -62dBm @MCS11;802.11ax 80MHz: -58dBm @MCS11
<b>SSIDs</b>	32 SSIDs total, 16 per radio (2.4GHz & 5GHz)
<b>Concurrent Clients</b>	256+
<b>Network Interfaces</b>	2x autosensing 10/100/1000 Base-T Ethernet Ports
<b>Auxiliary Ports</b>	1x Reset Pinhole
<b>Mounting</b>	Outdoor wall or pole mount, kits included
<b>LEDs</b>	1x tri-color LEDs for device tracking and status indication
<b>Network Protocols</b>	IPv4, IPv6, 802.1Q, 802.1p, 802.1x, 802.11e/WMM
<b>QoS</b>	802.11e/WMM, VLAN, TOS
<b>Network Management</b>	Embedded controller can manage up to 50 local GWN APs GWN.Cloud offers a free cloud management platform for unlimited GWN APs GWN Manager offers premise-based software controller for up to 3,000 GWN APs
<b>Power and Green Energy Efficiency</b>	PoE 802.3af/ 802.3at; Maximum Power Consumption: 12.9W
<b>Environmental</b>	Operation:-30°Cto 60°C Storage: -30°C to 70°C Humidity: 5% to 95% Non-condensing
<b>Physical</b>	Unit Dimension: 358.3mm(L)x115mm(W)x45.3mm(H); Unit Weight: 695g Entire Package Dimension: 275x185.5x89mm; Entire Package Weight: 995g
<b>Package Content</b>	GWN7660LR 802.11ax Wireless AP, Mounting Kits, Quick Installation Guide
<b>Weatherproof Grade</b>	IP66-level weatherproof capability when installed vertically
<b>Compliance</b>	FCC, CE, RCM, IC